



Traktor

Tractor

IMT-2050

INDUSTRIJA MAŠINA I TRAKTORA a.d. Beograd

4WD





IMT-2050 4WD agregatiran sa oruđima i priključnim mašinama služe za sve vrste radova u poljoprivredi i transportu. Odlikuju se lakim rukovanjem, a visok stepen unifikacije podsklopova i delova omogućava brzo i efikasno servisiranje. Traktori su opremljeni savremenom kabinom novog dizajna koja ispunjava sve zahteve konformnog rukovanja traktorom.



IMT-2050 4WD aggregated with attaching machines and implements, they are used for all kinds of work in agriculture and transport. They are known as easily operated machines and their high degree of unification of subassemblies and parts enables fast and efficient servicing. Tractors are equipped with modern cab which meets all the requirements of the comfortable operating

Specifications

IMT- 2050 4WD

| | | | |
|--|---|---|-----------------------------|
| Motor tip <i>Engine type</i> | Perkins 1103D - 33 | Vodom hlađeni, dizel sa direkt. ubrizgavanjem <i>Water cooled, direct injection diesel</i> | |
| | Radna zapremina <i>Capacity</i> | litre | 3,3 |
| Snaga motora <i>Engine power</i> | Nominalna snaga <i>Nominal power (97/68/EC)</i> | kW | 36,9 |
| | Nominalni br. obrtaja <i>Nominal speed</i> | min ⁻¹ <i>r.p.m</i> | 2200 |
| Menjač <i>Transmission</i> | Broj stepeni prenosa <i>Number of gears</i> | Hod napred <i>Forward</i> | Hod nazad <i>Reverse</i> |
| | Potpuno sinhronizovan <i>Fully synchronized</i> | 10 | 2 |
| Spojnica <i>Clutch</i> | Dvostepena suva <i>Dry dual friction disc type</i> | | |
| Priključno vratilo <i>P.T.O. Shaft</i> | Polunezavisno, proporcionalno kretanju traktora <i>Semi independent, and proportional ground speed</i> | | |
| | Ožljebljeno <i>Splined</i> | mm | 34.9 |
| | Broj obrtaja <i>Speed</i> | min ⁻¹ <i>r.p.m</i> | 540 or 1000 |
| Kočnice <i>Brakes</i> | Diskosne, potopljene u ulju <i>Disc type, Wet oil service brakes</i> | | |
| Upravljački mehanizam <i>Steering</i> | Hidrostatički <i>Hydrostatic</i> | | |

| | | | |
|---|--|---------|-----------|
| Hidraulički sistem <i>Hydraulics</i> | Sila dizanja <i>Lift capacity</i> | kN | 19,3 |
| Pneumatici <i>Tires</i> | Prednji <i>Front</i> | 7.50-20 | |
| | Zadnji <i>Rear</i> | 13.6-28 | |
| Razmak točkova <i>Wheel track</i> | Prednji <i>Front</i> | mm | 1300-1900 |
| | Zadnji <i>Rear</i> | | 1300-1900 |
| Gabaritne dimenzije <i>Overall dimensions</i> | Dužina <i>Length</i> | mm | 3230 |
| | Širina <i>Width</i> | | 1665 |
| | Visina <i>Height</i> | | 2310 |
| | Min.rastoj. od tla <i>Clearance</i> | | 290 |
| Međuosno rastojanje <i>Wheelbase</i> | mm | 1960 | |
| Rezervoar goriva <i>Fuel tank capacity</i> | litre | 60 | |
| Masa traktora <i>Tractor mass</i> | kg | 2350 | |

INDUSTRIJA MAŠINA I TRAKTORA a.d. Beograd, "u restrukturiranju"

11070 Novi Beograd, Zemunska 26

Telefon: +381 11 2154-677

+381 11 2151-114

Telefax: +381 11 2154 575

e-mail: office@imt.co.rs

www.imt.co.rs

