



Traktor

Tractor

IMT-5106/5136

INDUSTRIJA MAŠINA I TRAKTORA a.d. Beograd

4WD





Savremeni, estetski oblikovani traktori sa novim tehničkim rešenjima i ergonomskim pogodnostima. Prilagođen za agregatiranje i rad sa široko zahvatnim nošenim, polunošenim ili vučenim priključnim oruđima kategorije II i III.

Lako podizanje bočnih strana limarije omogućava brz prilaz svim delovima motora što olakšava rad i skraćuje vreme servisiranja.

Po želji kupca traktor je opremljen uređajem za elektronsko - hidrauličnu regulaciju položaja i vučnog otpora - EHR - firme BOSCH. Ovim se dobija brza i optimalna obrada signala čime se postiže kvalitetna obrada zemljišta uz ekonomično korišćenje traktora.



Modern, esthetically formed tractors with new technical solutions and ergonomical facilities. It has been adjusted for attachment and work with implements of large working width, mounted, semi-mounted of category II and III.

Easy removal of the sides of the body enables fast access to all engine parts which facilitates work and reduces time of servicing.

Upon special request the tractor can be equipped with electronic-hydraulic regulation of position and draft -EHR-manufactured by BOSCH. This provides fast automatic regulation thus achieving quality cultivation of soil with economical exploitation of the tractor.

Tehnički podaci

IMT- 5106 4WD

IMT- 5136 4WD

Specifications

Motor tip <i>Engine type</i>	IMT-5106	IMR S46/T	Četvorotaktni dizel <i>Four-stroke, Diesel</i>	
	IMT-5136	IMR TS46/T	Četvorotaktni dizel sa turbo kompresorom <i>Four-stroke, Diesel turbocharged</i>	
Snaga motora <i>Engine power</i>	Nominalna snaga <i>Nominal power</i>	kw	IMT-5106	77
			IMT-5136	99,5
	Nominalni br. obrtaja <i>Nominal speed</i>	min ⁻¹ <i>r.p.m</i>	2250	
Menjač <i>Transmission</i>	Broj stepeni prenosa <i>Number of gears</i>		Hod napred <i>Forward</i>	Hod nazad <i>Reverse</i>
	Delimično sinhronizovan <i>Partly synchronized</i>		10	2
	Sa pužnim brzinama <i>With creeper speeds</i>		12	4
Spojnica <i>Clutch</i>	Jednostepena <i>Single</i>			
Priključno vratilo <i>P.T.O. Shaft</i>	Ožljebljeno <i>Splined</i>	mm	34.9	
	Broj obrtaja <i>Speed</i>	min ⁻¹ <i>r.p.m</i>	540/1000	
Kočnice <i>Brakes</i>	Diskosne, potopljene u ulju <i>Oil immersed disc brakes</i>			
Upravljački mehanizam <i>Steering</i>	Hidrostatički <i>Hydrostatic</i>			

Hidraulički sistem <i>Hydraulics</i>	Sila dizanja <i>Lift capacity</i>	kN	38
Pneumatici <i>Tires</i>	Prednji <i>Front</i>	12.4-24	
	Zadnji <i>Rear</i>	18.4-38	
Razmak točkova <i>Wheel track</i>	Prednji <i>Front</i>	mm	1600-2000
	Zadnji <i>Rear</i>		1700-2100
Gabaritne dimenzije <i>Overall dimensions</i>	Dužina <i>Length</i>	mm	4820
	Širina <i>Width</i>		2270
	Visina <i>Height</i>		2820
	Min. rastoj. od tla <i>Clearance</i>		380
Masa traktora <i>Tractor mass</i>	IMT-5106 4WD	kg	6000
	IMT-5136 4WD		6040

INDUSTRIJA MAŠINA I TRAKTORA a.d.

Beograd, "u restrukturiranju"

11070 Novi Beograd, Zemunska 26

Telefon: +381 11 2154-677

+381 11 2151-114

Telefax: +381 11 2154 575

e-mail: office@imt.co.rs

www.imt.co.rs

