



Prednji traktorski utovarivači

Front tractor loader

Zadnji traktorski viljuškari

Tractor forklift-rear

INDUSTRIJA MAŠINA I TRAKTORA a.d. Beograd

IMT- 618.728

IMT- 618.733



IMT- 618.12

IMT- 618.22



Tehnički podaci

IMT- 618.728

IMT- 618.733

Specifications

Visina istresanja	mm	2400	2200	Unloading height
Dubina kopanja	mm	120	150	Digging depth
Ugao otvaranja kašike		35 ⁰	40 ⁰	Bucket opening angle
Ugao zatvaranja kašike		29 ⁰	30 ⁰	Bucket closing angle
Nosivost	daN	500	750 (1000*)	Capacity
Masa utovarivača* sa nosačem i korpom	kg	930	1220	Mass with loader and bucket

*Nosivost agregata od 1000daN se može ostvariti ako se koristi traktor sa prednjim pneumaticima 12,4-24 na tragu od 1700mm

*Aggregate capacity of 1000 daN can be achieved if used tractor with the following tyre dimensions: front tires 12.4-24 on toe-in of 1700 mm



Izborom radnih priključaka utovarivači imaju veliku primenu u svim oblastima poljoprivrede. Jednostavna i brza montaža utovarivača na traktor, brza zamena priključaka, jednostavna konstrukcija, minimalno održavanje su posebne odlike utovarivača. Utovarivač IMT-618.733 ima paralelno kretanje priključaka u toku dizanja. Agregatiranje IMT-618.728 vrši se na traktore IMT-542 4WD i IMT-549 4WD, a IMT-618.733 na IMT-560 4WD i IMT-577 4WD. Traktori moraju biti opremljeni spoljnom hidraulikom u okviru koje je razvodnik sa dva bloka (odnosno 4 izvoda).



Due to a selection of attachments, loader has a wide use in all agricultural works IMT-618.773 is aggregated with tractors IMT-560 4WD and IMT-577 4WD. It is easily and quickly mounted to tractors, attachments can be quickly changed, desing is simple and maintenance is minimal. It has hydraulic parallel moving of attachments while lifting. IMT-618.728 is aggregated with tractors IMT-542 4WD and IMT-549 4WD. The tractors must be outfitted with external hydraulics that includes distributor with two blocks (i.e. 4 outlets).

Tehnički podaci

IMT- 618.12

IMT- 618.22

Specifications

Max. visina dizanja viljuške	cm	250	250	Max. load lifting height
Naginjanje viljuške ka traktoru		10 ⁰	10 ⁰	Incline angle towards the tractor
Naginjanje viljuške od traktora		5 ⁰	5 ⁰	Incline angle from the tractor
Bočno pomeranje viljuške	cm	±10	±10	Side adjusment
Pritiskivač tereta		nema	ima	Press down board
Nosivost	daN	1000	1000	Capacity
Masa	kg	470	575	Mass



Pogodni su za utovar i istovar paletizovanih tereta u poljoprivredi, građevinarstvu i industriji. Prednost nad klasičnim viljuškama pokazuju u radu na otvorenom prostoru na neravnom i neuređenom terenu. Varijanta viljuškara IMT-618.22 je posebno prilagođena za rad u poljoprivredi jer poseduje pritiskivač boks paleta. Rukovanje je jednostavno i vrši ga traktorista sa sedišta. Nosivost zavisi od traktora kojim se vrši agregatiranje IMT-539 i IMT-549 nosivost 800daN, IMT-560 i IMT-577 nosivost 1000daN. Zadnji traktorski viljuškar može da se montira na traktore bez kabina sa vertikalnim izduvnim luncem.



Designed for loading and unloading materials stacked on pallets for transportation. It provides an excellent work in various areas including agriculture, civil engineering and industry. Among many advantages, they are reliable, safe and suitable for work in agriculture, having a hold down frame for stacked materials. The one - man operated implement is very simple and easy to use. When attached to IMT-539 and IMT-542, its carrying capacity is 800daN while with IMT-560 and IMT-577 it is 1000daN. Forklifts can be mounted to tractors without cab, but with vertically mounted muffler.



INDUSTRIJA MAŠINA I TRAKTORA a.d.

Beograd, "u restrukturiranju"

11070 Novi Beograd, Zemunska 26

Telefon: +381 11 2154-677

+381 11 2151-114

Telefax: +381 11 2154 575

e-mail: office@imt.co.rs

www.imt.co.rs